

CHRONO R 29 (SPE), BRITISH RACING GREEN/ÖHLINS YELLOW, 2022

obj. č: 010.22016SPE



Sugerowana cena

9.359 zł

Specyfikacje techniczne

produkowane rozmiary

S: 395mm / M: 430mm / L: 470mm / XL: 520mm

waga

12,5 Kg

rama

Chrono 29 6061 Xtralite Alloy butted, XC Forward Geometry, 73mm BSA bottom bracket, tapered head tube, HHG Internal Cable Routing, Boost 12x148mm rear axle

widelec

Fox 32 29 Float FIT GRIP EVOL Rhythm, 100mm, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: remote 2pos Push-unlock, low-speed rebound, air preload. Fox single pull

stery

Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

przerzutka

Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

manetki

Sram Trigger SX Eagle, 12s, X-Actuation 1:1

klamki hamulca

Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings

uchwyty

Truvativ Stylo 6K Eagle, 12s, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm

support

Sram DUB BSA, sealed bearings, 73mm

kierownica

Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 740mm, 9° backsweep, 0° upsweep, 31.8mm barbare

mostek

Onoff Sulfur, 6061 T6 Alloy, 31.8mm barbare, rise: +/-7°, length: sizes S/M: 60mm, size L: 80mm, size XL: 90mm

sztyca

Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 27.2mm, length 400mm

siodełko

Mondraker XC Series, steel rail

piasta przednia

Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts

tylna piasta

Formula MST148S-4SB, Boost 12x148mm, sealed bearings, IS 6 bolts

łańcuch

Sram SX Eagle, 12s, Powerlock

kaseta

Sram PG-1210, 11-50T, 12s

szprychy

CN round stainless steel

rafki

MDK-XP1 29 TLR, 25mm internal width, tubeless ready, 32 spokes

obudowa

Maxxis Ikon 29x2.20, 60TPI, wire bead. Maxxis Ikon 29x2.20, 60TPI, wire bead

zamówienie numer

010.22016SPE

gripy

Onoff Diamond, 1lock-on, 135mm

przedni hamulec

Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

tylny hamulec

Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

korba

34T, steel, X-Sync 2

mocowanie przerzutki

Mondraker M068

Galeria