

F-PLAY 26, DEEP PURPLE/BLACK/LIGHT BLUE, 2023

obj. č: 010.23211

Sugerowana cena

17.499 zł



Specyfikacje techniczne

produkowane rozmiary One size: 350mm	rama F-Play 26 6061 Alloy Stealth evo, hydroformed tubing, Zero Suspension System, 120mm travel, one piece bolt-on upper link, integrated internal non-removable battery, Tapered head tube, HHG internal cable routing, BSA bottom bracket, QR 9mm rear axle, 1x drivetrain compatible
widelec X-Fusion Velvet RL 26, 120mm, air spring, tapered steerer tube, 9x100mm axle, 32mm aluminum stanchions, 41mm offset. Settings: lockout, rebound, air preload	stery Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
przerzutka Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1	manetki Sram Trigger SX Eagle, 12s, X-Actuation 1:1
klamki hamulca Sram Level, tooled reach adjust, lever pivot bushings	uchwyty Sram SX Eagle, DUB axle, Direct mount chain ring, 155mm
support Sram DUB BSA, sealed bearings, 73mm	kierownica MDK XC 1.0, 6061 alloy, rise: 25mm, width: 680mm, 9° backsweep, 5° upsweep, 31.8mm barbare
mostek Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare	szttyca MDK XC 0-R, 6061 T6 Alloy, diameter 31.6mm, length 350mm
siodełko SDG Fly JR	piasta przednia Formula DC20LW, 9x100mm, cup cone ball bearings, IS 6 bolts
tylna piasta Mahle-Ebikemotion X-35	łańcuch Sram SX Eagle, 12s, Powerlock
kaseta Sram XG-1230, 11-50T, 12s	szprychy CN round stainless steel
rafki MDK-XP1 26 TLR, 25mm internal width, tubeless ready, 32 spokes	obudowa Kenda Booster 26x2.4 single compound 30TPI, wire bead
zamówienie numer 010.23211	gripy Onoff Twin, 1lock-on
amortyzator X-Fusion 02PRO R, 210x55mm. Settings: low-speed rebound, air preload. 45x8mm top and bottom bushings	przedni hamulec Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
tylny hamulec Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	regulacja amortyzatora A-Tune light compression
korba 30T, steel, X-Sync	mocowanie przerzutki Mondraker M073

silnik + akumulator

Mahle-Ebikemotion X-35, Mahle-Ebikemotion Internal 250Wh,
Mahle-Ebikemotion

Galeria

