

RAZE CARBON RR MIND, RACING SILVER/ÖHLINS YELLOW, 2022

obj. č: 010.22308



Sugerowana cena

38.999 zł

Specyfikacje techniczne

produkowane rozmiary S: 380mm / M: 420mm / L: 450mm / XL: 500mm	rama New Trail 29 Stealth Air full Carbon, Zero Suspension System, 130mm travel, Forward Geometry, Carbon Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors.
widelec Fox 36 29 Float GRIP2 Factory Kashima, 150mm, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload	stery "Acros custom for 1-1/2"" head tube, angular contact bearings 40x52x7, Internal cable routing"
przerzutka Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	manetki Sram Trigger GX Eagle, 12s, X-Actuation 1:1
klamki hamulca Sram G2 RS, SwingLink, tool-free reach adjust	uchwyty Sram X1 Carbon Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm
support Sram DUB BSA, sealed bearings, 73mm	kierownica Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
mostek Onoff Krypton FG 30mm, CNC, 31.8mm barbare	szttyca Fox Transfer Factory Kashima internal, diameter 31.6mm, S size: 363.5x125mm, M size: 418.3x150mm, L/XL size: 475.1x175mm
siodełko Fizik Antares R7	piasta przednia DT 350, Boost 15x110mm, IS 6 bolts
tylna piasta Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead	łańcuch Sram GX Eagle, 12s, Powerlock
kaseta Sram XG-1275, 10-52T, 12s	szprychy DT Competition, straightpull
rafki DT Swiss XM1700 Spline 29, 30mm internal width, welded aluminum, tubeless ready, 28 spokes	obudowa Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead, Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead
zamówienie numer 010.22308	gripy Onoff Diamond, 1lock-on, 135mm

amortyzator Fox Float DPS Factory Kashima evol LV, 205x57.5mm. Settings: Compression 3 positions lever, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 30x8mm bottom bushings	przedni hamulec Sram G2 RS, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads
tylny hamulec Sram G2 RS, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads	regulacja amortyzatora Light compression, extralight rebound, air volume spacer 0.6
korba 32T, CNC-machined alloy, X-SYNC 2	mocowanie przerzutki Sram UDH

Galeria

