SUMMUM CARBON R MX MIND, CARBON/FROST GREEN/YELLOW, 2022

obj. č: 010.22100



Sugerowana cena
40.039 zł

Specyfikacje techniczne

produkowane rozmiary
S / M / L / XL 29

rama
Summum Carbon Stealth Air full Carbon, Zero Suspension System, 200mm travel, Forward Geometry, Carbon Monoblock upper link, SuperBoost 12x157mm rear axle, 83mm BSA bottom bracket, HHG internal cable routing, MAX. capacity dual raw Enduro bearings, shock mudguard, ISCG 05, custom frame protectors. *Optional Geometry kit

widelec
Fox 40 29 Float FIT GRIP EVOL Performance, 203mm, air spring, 1-1/8” steerer tube, 20x110mm axle, offset 56mm. Settings: low-speed compression, low-speed rebound, air preload

stery
Onoff Mercurium 1.5 ZS for 1-1/8” steerer tube, 41x30.15x7x45ºx45º ACB sealed bearings, geometry kit cups, external diameter 56mm

przerzutka
Sram GX DH, 7s, medium cage, X-actuation 1:1

manetki
Sram trigger GX DH 7s, X-actuation 1:1

klamki hamulca
Sram Code R, tool-free reach adjust

uchwyty
Truvativ Descendant DH, DUB axle, Direct mount chain ring, 165mm

support
Sram DUB BSA, sealed bearings, 83mm

kierownica
Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9º backsweep, 5º upsweep, 31.8mm barbore

mostek
Onoff Krypton DH CNC Integrated FG, 25-30mm adjustable length, 31.8mm barbore, 6061 alloy, 2x6mm spacer

sztyca
SDG Micro I-Beam SP-751 Alloy, diameter 31.6mm, length 300mm, micro-adjustment

siodełko
SDG I-Fly 2.0 I-Beam, high-density PU foam, Cordura sides

piasta przednia
e*thirteen Boost 20x110mm, triple-sealed, fully machined aluminum, IS 6 bolts

łańcuch
Sram PC1110 11s, Powerlock

kaseta
Sram PG 720 11-25T, 7s

szprychy
e*thirteen custom Hive triple-butted black alloy, alloy nipples, nipple washers

rafki
e*thirteen LG1 Plus DH, IW29 29

obudowa
Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead, Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead

zamówienie numer
010.22100

gripy
Onoff Diamond, 1lock-on, 135mm

amortyzator
Fox DHX2 Performance Elite, 225x70mm. Settings: low-speed compression, low-speed rebound, spring preload. Trunnion top mount, 30x8mm bottom bushings

przedni hamulec Sram Code R, oversized 4-piston caliper, Centerline 203mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	**tylny hamulec** Sram Code R, oversized 4-piston caliper, Centerline 203mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
regulacja amortyzatora ECC010 compression, ECR012 rebound. Spring rate: S size 400 lbs, M size 450 lbs, L/XL size 500 lbs	**korba** 34T, steel, X-SYNC
inne *Optional geometry kit: +-1º / +-2º headset cups	