# SUMMUM CARBON R MX MIND, CARBON/FROST GREEN/YELLOW, 2022

*obj. č: 010.22100*



## Specyfikacje techniczne

**produkowane rozmiary**
S / M / L / XL 29

**rama**
Summum Carbon Stealth Air full Carbon, Zero Suspension System, 200mm travel, Forward Geometry, Carbon Monoblock upper link, SuperBoost 12x157mm rear axle, 83mm BSA bottom bracket, HHG internal cable routing, MAX. capacity dual raw Enduro bearings, shock mudguard, ISCG 05, custom frame protectors. *Optional Geometry kit

**widelec**
Fox 40 29 Float FIT GRIP EVOL Performance, 203mm, air spring, 1-1/8” steerer tube, 20x110mm axle, offset 56mm. Settings: low-speed compression, low-speed rebound, air preload

**stery**
Onoff Mercurium 1.5 ZS for 1-1/8” steerer tube, 41x30.15x7x45ºx45º ACB sealed bearings, geometry kit cups, external diameter 56mm

**przerzutka**
Sram GX DH, 7s, medium cage, X-actuation 1:1

**manetki**
Sram trigger GX DH 7s, X-actuation 1:1

**klamki hamulca**
Sram Code R, tool-free reach adjust

**uchwyty**
Truvativ Descendant DH, DUB axle, Direct mount chain ring, 165mm

**support**
Sram DUB BSA, sealed bearings, 83mm

**kierownica**
Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9º backsweep, 5º upsweep, 31.8mm barbore

**mostek**
Onoff Krypton DH CNC Integrated FG, 25-30mm adjustable length, 31.8mm barbore, 6061 alloy, 2x6mm spacer

**sztyca**
SDG Micro I-Beam SP-751 Alloy, diameter 31.6mm, length 300mm, micro-adjustment

**siodełko**
SDG I-Fly 2.0 I-Beam, high-density PU foam, Cordura sides

**piasta przednia**
e*thirteen Boost 20x110mm, triple-sealed, fully machined aluminum, IS 6 bolts

**łańcuch**
Sram PC1110 11s, Powerlock

**kaseta**
Sram PG 720 11-25T, 7s

**szprychy**
e*thirteen custom Hive triple-butted black alloy, alloy nipples, nipple washers

**rafki**
e*thirteen LG1 Plus DH, IW29 29

**obudowa**
Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead, Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead

**zamówienie numer**
010.22100

| | |
|---|---|
| **gripy**<br>Onoff Diamond, 1lock-on, 135mm | **amortyzator**<br>Fox DHX2 Performance Elite, 225x70mm. Settings: low-speed compression, low-speed rebound, spring preload. Trunnion top mount, 30x8mm bottom bushings |
| **przedni hamulec**<br>Sram Code R, oversized 4-piston caliper, Centerline 203mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads | **tylny hamulec**<br>Sram Code R, oversized 4-piston caliper, Centerline 203mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads |
| **regulacja amortyzatora**<br>ECC010 compression, ECR012 rebound. Spring rate: S size 400 lbs, M size 450 lbs, L/XL size 500 lbs | **korba**<br>34T, steel, X-SYNC |
| **inne**<br>*Optional geometry kit: +-1º / +-2º headset cups | |