

# F-PODIUM DC CARBON, BLUE/WHITE/ORANGE, 2021

obj. č. 010.21049



Sugerowana cena

**23.299 zł**

## Specyfikacje techniczne


<b>produkowane rozmiary</b> S 390mm / M 420mm / L 470mm / XL 510mm	<b>waga</b> 12,4 Kg
<b>rama</b> F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 100mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.	<b>widelec</b> Rockshox SID Select RL 29, 120mm, Charger, Debonair, tapered steerer tube, Boost 15x110mm axle, 35mm tapered aluminum stanchions, offset 44mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload
<b>stery</b> Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom	<b>przerzutka</b> Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
<b>manetki</b> Sram Trigger SX Eagle, 12s, X-Actuation 1:1	<b>klamki hamulca</b> Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings
<b>uchwyty</b> Truativ Stylo 6K Eagle, 12s, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm	<b>support</b> Sram DUB BSA, sealed bearings, 73mm
<b>kierownica</b> Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9 backsweep, 0 upsweep, 31.8mm barbore Onoff Twin, 1lock-on, 135mm	<b>mostek</b> MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm
<b>sztyca</b> Onoff Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M/L/XL size 387x125mm	<b>siodełko</b> Fizik Antares R7
<b>piasta przednia</b> DT 370, Boost 15x110mm, IS 6 bolts	<b>tylna piasta</b> DT 370, Boost 12x148mm, 3 Pawl system, IS 6 bolts
<b>łańcuch</b> Sram SX Eagle, 12s, Powerlock	<b>kaseta</b> Sram PG-1230, 11-50T, 12s
<b>szprychy</b> DT Champion, straightpull	<b>rafki</b> DT Swiss X1900 Spline 29, 25mm internal width, sleeved aluminum, tubeless ready, 28 spokes
<b>obudowa</b> Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead	<b>zamówienie numer</b> 010.21049
<b>amortyzator</b> Rockshox SID Select+ RLR Debonair, 185x47.5mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings	<b>przedni hamulec</b> Sram Level T, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad
<b>tylny hamulec</b> Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	<b>owijka</b> Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead

**regulacja amortyzatora**  
Light compression, medium rebound, Lockout 430, 1 Token

**korba**  
34T, steel, X-Sync 2

**mocowanie przerzutki**  
Sram UDH

## Geometria



### GEOMETRY

Size	S	M	L	XL
<b>A</b> Seat Tube Length	390 mm	420 mm	470 mm	510 mm
<b>B</b> Top Tube Length	583 mm	603 mm	629 mm	654 mm
<b>C</b> Bottom Bracket Drop	-31 mm	-31 mm	-31 mm	-31 mm
<b>D</b> Bottom Bracket Height	337 mm	337 mm	337 mm	337 mm
<b>E</b> Chainstay Length	432 mm	432 mm	432 mm	432 mm
<b>F</b> Seat Tube Angle, Actual	70.8°	70.8°	70.8°	70.8°
<b>G</b> Seat Tube Angle, Effective	75.1°	75.1°	75.1°	75.1°
<b>H</b> Head Tube Angle	66.8°	66.8°	66.8°	66.8°
<b>I</b> Fork Offset	44 mm	44 mm	44 mm	44 mm
<b>J</b> Wheelbase	1146 mm	1167 mm	1191 mm	1217 mm
<b>K</b> Head Tube Length	85 mm	90 mm	100 mm	115 mm
<b>L</b> Reach	430 mm	450 mm	470 mm	490 mm
<b>M</b> Stack	577mm	582mm	591 mm	605mm