PRIME R (SPE), CHERRY RED/BLACK, 2022

obj. č: 010.22142SPE



Sugerowana cena
23.919 zł
Aktualna cena
17.999 zł

Specyfikacje techniczne

produkowane rozmiary
XS: 380mm / S: 390mm / M: 430mm / L: 470mm / XL: 510mm

waga
22,8 Kg

rama
Prime Xtralite 6061 Full Butted Alloy, Forward Geometry, intenal non-removable battery, tapered head tube, Boost 12x148mm rear axle, integrated dropout speed sensor

widelec
Marzocchi Z2 29 Rail, 120mm, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: sweep adjust compression, Low-speed rebound, air preload

stery
Onoff Saturn tapered for 1-1/8” to 1-1/2” head tube, ACB sealed bearings, top 41x30.2x7x45ºx45º, bottom 51.9x40x8x45ºx45º

przerzutka
Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1

manetki
Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click

klamki hamulca
Sram G2 R, tool-free reach adjust

uchwyty
Race Face Aeffect ebike, 165mm

kierownica
Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9º backsweep, 5º upsweep, 31.8mm barbore

mostek
Onoff Sulfur FG 30mm 0º, 6061 forged alloy, 31.8mm barbore

sztyca
Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

siodełko
FIZIK Terra Aidon X5 145mm

piasta przednia
Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts

tylna piasta
Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts

łańcuch
Sram SX Eagle, 12s, Powerlock

kaseta
Sram PG-1210, 11-50T, 12s

szprychy
CN round stainless steel

rafki
MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes

obudowa
Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead, Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead

zamówienie numer
010.22142SPE

gripy
Onoff Diamond, 1lock-on, 135mm

przedni hamulec
Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

tylny hamulec
Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

korba
Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

mocowanie przerzutki
Mondraker M068

silnik + akumulator
Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3 , Bosch Powertube 750Wh, Bosch Kiox 300

Galeria



