

PODIUM CARBON 29 (SPE), TRANSLUCENT RED CARBON/CHERRY RED, 2022

obj. č: 010.22032SPE



Specyfikacje techniczne

produkowane rozmiary S: 390mm / M: 420mm / L: 470mm / XL: 510mm	waga 9,6 Kg
rama Podium 29 Stealth Air Carbon, XC Forward Geometry, BSA bottom bracket, tapered head tube, HHG internal cable routing, Boost 12x148mm rear axle, dedicated 1X drivetrain design, Flatmount brake compatible,	widelec Fox 32 Step Cast Float Grip Evol Performance, 100mm, tapered steerer tube, 15x110mm Boost axle, offset 44mm. Settings: remote 2pos Push-unlock, rebound, air preload. Fox single pull
stery Onoff Titan tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41.8x30.5x8x45°x45°, bottom 51.9x40x8x45°x45°	przerzutka Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1
manetki Sram Trigger GX Eagle, 12s, X-Actuation 1:1	klamki hamulca Sram Level TL, Direct Link actuation, tooling reach adjust, lever pivot bushings
uchwyty Sram GX Eagle, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm	support Sram DUB BSA, sealed bearings, 73mm
kierownica Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm bar bore	mostek MDK, 6061 T6 Alloy, 31.8mm bar bore, rise: +/-5°, length: sizes S/M: 60mm, size L: 70mm, size XL: 80mm
szttyka Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 27.2mm, length 400mm	siodełko Fizik Antares R7
piasta przednia Mavic, Boost 15x110mm, IS 6 bolts	tylna piasta Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts
łańcuch Sram NX Eagle, 12s, Powerlock	kaseta Sram XG-1275, 10-50T, 12s
szprychy Mavic straightpull double butted, contactless lacing	rafki Mavic Crossmax 29, 25mm internal width, welded rim, hookless, tubeless ready, 24 spokes
obudowa Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead, Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead	zamówienie numer 010.22032SPE

gripy

Onoff Diamond, 1lock-on, 135mm

przedni hamulec

Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

tylny hamulec

Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

korba

34T, CNC-machined alloy, X-SYNC 2

mocowanie przerzutki

Sram UDH

Galeria