

# F-PLAY 24, ORANGE/BLACK, 2023

obj. č: 010.23210

Sugerowana cena

16.499 zł



## Specyfikacje techniczne

|                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                   |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>produkowane rozmiary</b><br>One size: 300mm                                                                                                                                 | <b>rama</b><br>F-Play 24 6061 Alloy Stealth evo, hydroformed tubing, Zero Suspension System, 120mm travel, one piece bolt-on upper link, integrated internal non-removable battery, Tapered head tube, HHG internal cable routing, BSA bottom bracket, QR 9mm rear axle, 1x drivetrain compatible |
| <b>widelec</b><br>X-Fusion Velvet RL 26, 100mm, air spring, tapered steerer tube, 9x100mm axle, 32mm aluminum stanchions, 41mm offset. Settings: lockout, rebound, air preload | <b>stery</b><br>Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°                                                                                                                                                         |
| <b>przerzutka</b><br>Sram GX, 10s, short cage, X-actuation 1:1                                                                                                                 | <b>manetki</b><br>Sram trigger GX 10s, X-actuation 1:1                                                                                                                                                                                                                                            |
| <b>klamki hamulca</b><br>Sram Level, tooling reach adjust, lever pivot bushings                                                                                                | <b>uchwyty</b><br>Samox DM 30T steel, 152mm                                                                                                                                                                                                                                                       |
| <b>support</b><br>BSA, 73mm                                                                                                                                                    | <b>kierownica</b><br>MDK XC 1.0, 6061 alloy, rise: 25mm, width: 680mm, 9° backsweep, 5° upsweep, 31.8mm bar bore                                                                                                                                                                                  |
| <b>mostek</b><br>Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm bar bore                                                                                                   | <b>sztyca</b><br>MDK XC 0-R, 6061 T6 Alloy, diameter 31.6mm, length 300mm                                                                                                                                                                                                                         |
| <b>siodełko</b><br>SDG Fly JR                                                                                                                                                  | <b>piasta przednia</b><br>Formula DC20LW, 9x100mm, cup cone ball bearings, IS 6 bolts                                                                                                                                                                                                             |
| <b>tylna piasta</b><br>Mahle-Ebikemotion X-35                                                                                                                                  | <b>łańcuch</b><br>Sram PC1031 10s, Powerlock                                                                                                                                                                                                                                                      |
| <b>kaseta</b><br>Sram PG 1020 11-36T, 10s                                                                                                                                      | <b>szprychy</b><br>CN round stainless steel                                                                                                                                                                                                                                                       |
| <b>rafki</b><br>MDK-XP1 24 TLR, 25mm internal width, tubeless ready, 32 spokes                                                                                                 | <b>obudowa</b><br>Kenda Booster 24x2.4 single compound 30TPI, wire bead                                                                                                                                                                                                                           |
| <b>zamówienie numer</b><br>010.23210                                                                                                                                           | <b>gripy</b><br>Onoff Twin, 1lock-on                                                                                                                                                                                                                                                              |
| <b>amortyzator</b><br>X-Fusion 02PRO R, 210x47.5mm. Settings: low-speed rebound, air preload. 45x8mm top and bottom bushings                                                   | <b>przedni hamulec</b><br>Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad                                                                                                                                                                      |
| <b>tylny hamulec</b><br>Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad                                                     | <b>regulacja amortyzatora</b><br>A-Tune light compression                                                                                                                                                                                                                                         |
| <b>korba</b><br>30T, steel                                                                                                                                                     | <b>mocowanie przerwutki</b><br>Mondraker M073                                                                                                                                                                                                                                                     |

### **silnik + akumulator**

Mahle-Ebikemotion X-35, Mahle-Ebikemotion Internal  
250Wh, Mahle-Ebikemotion

---

### **Galeria**

---

