

SUPERFOXY R, FROST GREEN/BLACK/ÖHLINS YELLOW, 2022

obj. č: 010.22076



Sugerowana cena

26.519 zł

Specyfikacje techniczne

produkowane rozmiary S: 380mm / M: 420mm / L: 470mm / XL: 510mm	rama SuperFoxy 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 160mm travel, Forward Geometry, one piece Monoblock upper link, SuperBoost 12x157mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, telescopic seatpost internal routing, Max. capacity sealed bearings, ISCG 05
widelec Öhlins RXF 38 M.2 29, 170mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber	stery Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°
przerzutka Sram NX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1	manetki Sram Trigger SX Eagle, 12s, X-Actuation 1:1
klamki hamulca Sram Code R, tool-free reach adjust	uchwyty Truvativ Descendant 7K Eagle, SuperBoost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm
support Sram DUB BSA, sealed bearings, 73mm	kierownica Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore
mostek Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore	sztyca Onoff Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M size 387x125mm, L size: 425x150mm, XL size: 465x170mm
siodełko SDG BEL-AIR 3.0, LPU foam, steel rails	piasta przednia Mavic, Boost 15x110mm, IS 6 bolts
tylna piasta Mavic, SuperBoost 12x157mm, ID360 Ratched system, IS 6 bolts	łańcuch Sram SX Eagle, 12s, Powerlock
kaseta Sram XG-1230, 11-50T, 12s	szprychy Mavic J-bend duble butted
rafki Mavic Custom Deemax 29, 28mm internal width, Maxtal welded rim, tubeless ready, 28 spokes	obudowa Maxxis Assegai 29x2.5WT, Maxxis Dissector 29x2.4WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding beadtubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead,
zamówienie numer 010.22076	gripy Onoff Diamond, 1lock-on, 135mm

amortyzator Öhlins TTX Air 205X65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings	przedni hamulec Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
tylny hamulec Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	regulacja amortyzatora C20 compression, R35 rebound
korba 32T, CNC-machined alloy, X-SYNC 2	mocowanie przerzutki Mondraker M068

Galeria

