PRIME 29 (SPE), MARLIN BLUE/BLACK, 2022

obj. č: 010.22179SPE



Sugerowana cena
21.399 zł

Specyfikacje techniczne

produkowane rozmiary
XS: 380mm / S: 390mm / M: 430mm / L: 470mm / XL: 510mm

waga
22,2 Kg

rama
Prime Xtralite 6061 Full Butted Alloy, Forward Geometry, intenal removable battery with integrated alloy cover, tapered head tube, Boost 12x148mm rear axle, integrated dropout speed sensor

widelec
RockShox Recon Silver RL 29, 120mm, Motion control, Solo Air, tapered steerer tube, Boost 15x110mm axle, 42mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload

stery
Onoff Saturn tapered for 1-1/8” to 1-1/2” head tube, ACB sealed bearings, top 41x30.2x7x45ºx45º, bottom 51.9x40x8x45ºx45º

przerzutka
Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1

manetki
Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click

klamki hamulca
Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings

uchwyty
Race Face Aeffect ebike, 165mm

kierownica
Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9º backsweep, 5º upsweep, 31.8mm barbore

mostek
Onoff Sulfur FG 30mm 0º, 6061 forged alloy, 31.8mm barbore

sztyca
Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 31.6mm, length 400mm

siodełko
FIZIK Terra Aidon X5 145mm

piasta przednia
Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts

tylna piasta
Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts

łańcuch
Sram SX Eagle, 12s, Powerlock

kaseta
Sram PG-1210, 11-50T, 12s

szprychy
CN round stainless steel

rafki
MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes

obudowa
Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead, Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead

zamówienie numer
010.22179SPE

gripy
Onoff Diamond, 1lock-on, 135mm

przedni hamulec
Sram Level TL, 2 piece caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pad

tylny hamulec
Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad

korba
Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

mocowanie przerzutki
Mondraker M068

silnik + akumulator
Bosch Performance Line CX Cruise (25Km/h) GEN4, Bosch Powertube 625Wh, Bosch Purion

Galeria



