

CHRONO 29, DIRTY WHITE/BLACK, 2022

obj. č: 010.22008



Sugerowana cena

7.019 zł

Specyfikacje techniczne

produkowane rozmiary

S: 395mm / M: 430mm / L: 470mm / XL: 520mm

rama

Chrono 29 6061 Xtralite Alloy butted, XC Forward Geometry, 73mm BSA bottom bracket, tapered head tube, HHG Internal Cable Routing, Boost 12x148mm rear axle

widelec

RockShox Judy Silver TK 29, 100mm, TurnKey, Solo Air, tapered steerer tube, 9x100mm axle, 30mm steel stanchions, 46mm offset. Settings: Poplock 2 pos remote compression (open/lock), rebound, air preload

stery

Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°

przerzutka

Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1

manetki

Sram Trigger SX Eagle, 12s, X-Actuation 1:1

klamki hamulca

Sram Level, tooled reach adjust, lever pivot bushings

uchwyty

Sram SX Eagle, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm

support

Sram DUB BSA, sealed bearings, 73mm

kierownica

Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 740mm, 9° backsweep, 0° upsweep, 31.8mm barbare

mostek

Onoff Sulfur, 6061 T6 Alloy, 31.8mm barbare, rise: +/-7°, length: sizes S/M: 60mm, size L: 80mm, size XL: 90mm

sztyca

Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 27.2mm, length 400mm

siodełko

Mondraker XC Series, steel rail

piasta przednia

Formula DC20LW, 9x100mm, cup cone ball bearings, IS 6 bolts

tylna piasta

Formula MST148S-4SB, Boost 12x148mm, sealed bearings, IS 6 bolts, MS freehub

łańcuch

Sram SX Eagle, 12s, Powerlock

kaseta

Sram PG-1210, 11-50T, 12s

szprychy

CN round stainless steel

rafki

MDK-XP1 29 TLR, 25mm internal width, tubeless ready, 32 spokes

obudowa

Maxxis Ikon 29x2.20, 60TPI, wire bead, Maxxis Ikon 29x2.20, 60TPI, wire bead

zamówienie numer

010.22008

gripy

Onoff Diamond, 1lock-on, 135mm

przedni hamulec

Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

tylny hamulec

Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad

korba

34T, steel, X-Sync 2

mocowanie przerzutki

Mondraker M068

Galeria

