

SUMMUM 29, DIRTY WHITE/DEEP PURPLE/FLAME RED, 2022

obj. č: 010.22080



Sugerowana cena

22.359 zł

Specyfikacje techniczne

produkowane rozmiary

S / M / L / XL 29

waga

17,9 kg

rama

Summum 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero suspension system, 200mm travel, Forward Geometry, alloy upper link with shock eyelet bearings, SuperBoost 12x157mm rear axle, 83mm BSA bottom bracket, MAX. capacity dual raw Enduro bearings, HHG internal cable routing, ISCG 05. *Optional Geometry kit

widelec

Rockshox Boxxer Select RC 29, 200mm, DebonAir, 1-1/8" steerer tube, Boost 20x110mm axle, offset 56mm. Settings: low-speed compression, rebound, air preload

stery

Onoff Mercurium 1.5 ZS for 1-1/8" steerer tube, 41x30.15x7x45°x45° ACB sealed bearings, geometry kit cups, external diameter 56mm

przerzutka

Sram X7, 9s, short cage, X-actuation 1:1

manetki

Sram trigger X5, 9s, X-actuation 1:1

uchwyty

Race Face Chester, alloy, 165mm

support

Race Face BSA, 83mm

kierownica

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore

mostek

Onoff Krypton DH CNC Integrated FG, 25-30mm adjustable length, 31.8mm barbore, 6061 alloy, 2x6mm spacer

szttyca

SDG Micro I-Beam SP-751 Alloy, diameter 31.6mm, length 300mm, micro-adjustment

siodełko

SDG I-Fly 2.0 I-Beam, high-density PU foam, Cordura sides

piasta przednia

MDK DA4371B-M20, Boost 20x110mm, IS 6 bolts

tylna piasta

MDK DA4352B, 12x157mm, sealed bearings, IS 6 bolts

łańcuch

Sram PC-951, 9s

kaseta

Sram PG-950, 11-26T, 9s

szprychy

CN stainless steel

rafki

MDK-DP1 29, 27mm internal width, 32 holes

obudowa

Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead, Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead

zamówienie numer

010.22080

gripy

Onoff Diamond, 1lock-on, 135mm

amortyzator

Fox Van RC Performance, 225x70mm. Settings: low-speed compression, low-speed rebound, spring preload. Trunnion top mount, 30x8mm bottom bushings

przedni hamulec

Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

tylny hamulec

Sram Code R, oversized 4-piston caliper, Centerline 203mm IS 6 bolts
one-piece rotor, steel-backed metal sintered pads

regulacja amortyzatora

Light compression, light rebound. Spring rate: S size 400
lbs, M size 400 lbs, L size 450 lbs, XL size 500 lbs

korba

36T, E.13 Vario Compact Upper Slider ,Alloy backplate ,DMB (Direct
mount Bashguard) Lower Slider 34-36t, ISCG 05 adjustable upper slider

mocowanie przerzutki

Mondraker M068

inne

*Optional geometry kit: $+1^{\circ}$ / $+2^{\circ}$ headset cups

Galeria