

FOXY 29, RACING SILVER/BLACK, 2022

obj. č: 010.22064



Sugerowana cena

19.239 zł

Specyfikacje techniczne

produkowane rozmiary S: 380mm / M: 420mm / L: 470mm / XL: 510mm	waga 15,5 Kg
rama Foxy 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 150mm travel, Forward Geometry, one piece Monoblock upper link, Boost 12x148mm rear axle, 73mm BSA bottom bracket, dedicated 1x drivetrain design, telescopic seatpost internal routing, MAX capacity sealed bearings, ISCG 05	widelec Fox 36 29 Float FIT GRIP EVOL Rhythm, 160mm, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: sweep adjust compression, low-speed rebound, air preload
stery Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°	przerzutka Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1
manetki Sram Trigger SX Eagle, 12s, X-Actuation 1:1	klamki hamulca Sram G2 R, tool-free reach adjust
uchwyty Sram SX Eagle, Boost, DUB axle, Direct Mount chain ring, S/M size: 170mm, L/XL size: 175mm	support Sram DUB BSA, sealed bearings, 73mm
kierownica Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare	mostek Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare
szttyca Onoff Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M size 387x125mm, L size: 425x150mm, XL size: 465x170mm	siodełko SDG BEL-AIR 3.0, LPU foam, steel rails
piasta przednia DT 370, Boost 15x110mm, IS 6 bolts	tylna piasta DT 370, Boost 12x148mm, 18T Ratched LN system, IS 6 bolts,
łańcuch Sram SX Eagle, 12s, Powerlock	kaseta Sram PG-1210, 11-50T, 12s
szprychy DT Champion, straightpull	rafki DT Swiss E1900 Spline 29, 30mm internal width, sleeved aluminum, tubeless ready, 28 spokes
obudowa Maxxis Minion DHF 29x2.5 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead, Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead	zamówienie numer 010.22064
gripy Onoff Diamond, 1lock-on, 135mm	amortyzator Fox Float DPS LV EVOL Performance, 205x62.5mm. Settings: rebound, 3-position compression adjustment (Open/Mid/Lock), air preload. Trunnion top mount, 22.2x10mm bottom bushings

przedni hamulec

Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

tylny hamulec

Sram G2 R, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

regulacja amortyzatora

Light compression, extralight rebound, air volume spacer 0.6

korba

32T, steel, X-Sync 2

mocowanie przerzutki

Mondraker M068

Galeria