LEVEL R (SPE), BLACK/DIRTY WHITE, 2022

obj. č: 010.22212SPE

Sugerowana cena
37.959 zł
Aktualna cena
25.599 zł

Specyfikacje techniczne

produkowane rozmiary
S: 380mm / M: 420mm / L: 450mm / XL: 490mm

waga
26,1 Kg

rama
Level 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 170mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers

widelec
Fox 38 29 Float FIT GRIP EVOL Performance, 180mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload

stery
Onoff Saturn tapered for 1-1/8” to 1-1/2” head tube, ACB sealed bearings, top 41x30.2x7x45ºx45º, bottom 51.9x40x8x45ºx45º

przerzutka
Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

manetki
Sram Trigger NX Eagle, 12s, X-Actuation 1:1, single click

klamki hamulca
Sram G2 RS, SwingLink and lever pivot bearings, tools-free reach and contact point adjust

uchwyty
Race Face Aeffect ebike, 165mm

kierownica
Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9º backsweep, 5º upsweep, 31.8mm barbore

mostek
Onoff Sulfur FG 30mm 0º, 6061 forged alloy, 31.8mm barbore

sztyca
Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

siodełko
FIZIK Terra Aidon X5 145mm

piasta przednia
Mavic, Boost 15x110mm, IS 6 bolts

tylna piasta
Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts

łańcuch
Sram SX Eagle, 12s, Powerlock

kaseta
Sram PG-1210, 11-50T, 12s

szprychy
Mavic J-bend duble butted, contactless lacing

rafki
Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes

obudowa
Maxxis Assegai 29x2.5WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead

zamówienie numer
010.22212SPE

gripy
Onoff Diamond, 1lock-on, 135mm

amortyzator
Fox DHX2 Performance Elite, 225x75mm. Settings: low-speed compression, low-speed rebound, spring preload. Trunnion top mount, 25x10mm bottom bushings

przedni hamulec
Sram G2 RS, 4-piston caliper, Centerline 220mm IS 6 bolts one-piece rotor, steel-backed organic pads

tylny hamulec
Sram G2 RS, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

regulacja amortyzatora
Medium compression, medium rebound. Spring rate: S/M size 300 lbs, L size 350 lbs, XL size 400 lbs

korba
Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

mocowanie przerzutki
Mondraker M068

silnik + akumulator
Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3 , Bosch Powertube 750Wh, Bosch Kiox 300

Galeria